



NOTES:

1. ALL FABRICATED METAL COMPONENTS SHALL BE STEEL SHOTBLASTED, ETCHED, PHOSPHATIZED, PREHEATED, AND ELECTROSTATICALLY POWDER-COATED WITH T.G.I.C. POLYESTER POWDER COATINGS. PRODUCTS SHALL BE FULLY CLEANED AND PRETREATED, PREHEATED AND COATED WHILE HOT TO FILL CREVICES AND BUILD FILM COATING. COATED PARTS SHALL THEN BE FULLY CURED TO COATING MANUFACTURER'S SPECIFICATIONS. THE THICKNESS OF THE RESULTING FINISH AVERAGES 8-10 MILS.
2. OIL IMPREGNATED BRONZE BUSHINGS AND STAINLESS STEEL PIVOT PINS FOR DOOR MOVEMENT, STAINLESS STEEL KEYED LOCK ASSEMBLY.
3. PERMANENTLY AFFIX TO THE GROUND PER MANUFACTURER'S INSTRUCTIONS. CONSULT YOUR LOCAL CODES FOR REGULATIONS.
4. PROVIDE PLASTIC INNER LINER MANUFACTURED BY TRASH RECEPTACLE MANUFACTURER.
5. CONTRACTOR SHALL PROVIDE ANCHOR BOLT.

N.T.S.

DEPARTMENT OF PUBLIC WORKS



STANDARD DETAIL

DATE: 6/12/19

DRAWN BY: LJPC

SHEET: 1 OF 1

PROWAG AND DOWNTOWN PROJECTS

STEEL TRASH RECEPTACLE